



DATASHEET

Speaker

MODEL NO: SVSA01

General Description-

general-purpose, cost-effective loudspeaker for indoor use

Prominent sound quality makes more reliable.

Single Unit for Speaker, Zero Noise, Good Sound Quality

Speaker Amplifier RCA Female & Audio Adjustment, 12V 1 Amp Power
Supply SPEAKER IC PAM8403 3W Output at 10% THD with a 4Ω Load and 5V
Power, Enclosure ABS Material, SPEAKER OHMS 4 OHMS, SPEAKER
WATTS 20W, Single RCA Connector

Main Features:

Easy installation

Good speech intelligibility and background music reproduction.

Available in Black.

ABS construction.

SPEAKER VALUME CONTROLLER

Crystal clear voice quality. (Speaker)

One-way communication from remote location via any DVR/NVR.

The board features compact size and low current consumption.

<u>Technical Specifications:</u>	
Type:	Type: One Way Audio Communicator Device.
Model:	Model: SVSA01
Application	Application One Way Audio FOR DVR/NVR
Operation Temperature Range	Operation Temperature Range -40 to +85
SPEAKER IC	SPEAKER IC PAM8403 3W X 3W Output at 10% THD with a 4Ω Load and 5V Power
Audio out	Single RCA Connector
Item Weight	390G
AUDIO PCB Dimensions	6.9 x 8.8 x 3.5 cm
Device Dimension	90mm X 90MM x 65
Mounting	Wall Mounting
Power Supply	12 V DC/ .5ma (Min)
Enclosure	ABS Material
Colour	Black
SPEAKER WATTS	20W
SPEAKER OHMS	4 OHMS
<u>Electrical</u>	
Rated Power	6W
Sound Pressure Level at 6W/1 W (1 kHz, 1 m)	96dB/88dB
Effective frequency range	150Hz to 15kHz
Opening angle horizontal(1kHz/ 4kHz,-6dB)	165°/95°
Connector	RCA Connector